

REVOLTA

SERIES




Traitement / Treatment / Tratamiento / Trattamento / Behandlung





Oléofuge
Oil-repellent
Oleófuga
Olio repellente
Ölabweisende



Hydrofuge
Water-repellent
Hidrófuga
Impermeabile
Wasserabweisende



Anti-poussière
Dust-repellent
Antisuciedad
Antimacchia
Staubabweisende



HS CODE

56090090

CARTON SIZE / PCS.

60 x 40 x 24 / 12

AET N°2777/10958-01/E04-01

Satra Technology Europe Ltd., N° 2777,
Bracetown Business Park, Clonee,
Dublin, D15YN2P, Ireland

MODULE D FI14/14003.02








SGS Fimko Oy, N°0598
Takomotie 8,
00380 HELSINKI, Finland

AET (UKCA) N°AB0321/16019-01/E01-01

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering
Northamptonshire, NN16 8SD, United Kingdom

MODULE D 11 IN14/14003

SGS United Kingdom Ltd., N°0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom

REF.	FA 30 309 20
 LG. KG	1.5 m / 2.0 m (connector included)
CE	EN 355:2002
MAT.	 45 mm  PES + Treatment
	---
	ALU
	NO
+	---
	0.99 KG



Largeur de l'absorbeur d'énergie
 Width of the energy absorber
Ancho del absorbedor de energía
 Larghezza del assorbitore di energia
 Breite des Falldämpfers

LG.



Longueur Poids maxi utilisateur
 Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Matière connecteur haut / connecteur bas
 Material of top connector / bottom connector
Material conector alto / conector bajo
 Materiale connettore alto / connettore basso
 Material oberes / unteres Verbindungselement



Ouverture
 Gate opening
Apertura
 Apertura
 Öffnung



Homologué pour le travail à proximité d'arêtes vives
 Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
 Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten