











FA 30 522 XX

P. 1 | 2



HS CODE
56090090
CARTON SIZE / PCS.
60 x 40 x 24 cm / 12
AET N° 2777/10963-02/E01-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland



REF.	FA 30 522 10	FA 30 522 15	FA 30 522 20
 LG. KG	1 m (connector included)	1.5 m (connector included)	2 m (connector included)
	140 KG		
CE	EN 355:2002		
MAT.	 PA 11 mm		
	45 mm		
	 FA 50 103 22 / FA 50 208 11		
	NO		
+	---		
	1.01 KG	1.05 KG	1.10 KG



**Largeur de l'absorbeur d'énergie**  
 Width of the energy absorber  
**Ancho del absorbedor de energia**  
 Larghezza del assorbitore di energia  
**Breite des Falldämpfers**



LG.  
 KG  
**Longueur Poids maxi utilisateur**  
 Length Max. user weight  
**Longitud Peso máximo del usuario**  
 Lunghezza Peso Max. dell'utente  
 Länge Höchstgewicht des Benutzers



**Matière connecteurs**  
 Material of connectors  
**Material de los conectores**  
 Materiale connettori  
**Material Verbinder**



**Homologué pour le travail à proximité d'arêtes vives**  
 Approved for work near sharp edges  
**Homologado para trabajo cerca de aristas vivas**  
 Omologato per lavoro in prossimità di spigoli vivi  
 Zugelassen für Arbeiten in der Nähe scharfer Kanten